


FARM LED




Brida
Clamp
Collier



ANTIVANDÁLICA / ANTIVANDALISM / ANTIVANDALISME



APLICACIONES INDICADAS / SUITABLE APPLICATIONS / APPLICATIONS APPROPRIÉES





RG 0/1

MACADAM

3/4

UGR
<19

CR>80


L70B50
>
50.000

IK10

IP69K

CE

EN 60598-1



Ref.	Tamaño Size Dimension	Potencia Power Puissance	Emisión bruta Gross output Flux de la source	Emisión Neta Net output Flux sortant	Tª color Tª colour Tª couleur	L	D	D + brida D + clamp D + fixations	Embalaje Packaging Emballage
	(mm)	(W)	(Lm)	(Lm)	(°K)	(mm)	(mm)	(mm)	
Q0795	600	13	1.490	1.155	3.000	763	100	120	1
Q0899	600	13	1.550	1.201	4.000	763	100	120	1
Q0900	600	16	2.560	1.984	3.000	763	100	120	1
Q0955	600	16	2.670	2.070	4.000	763	100	120	1
Q0796	1200	24	2.980	2.310	3.000	1.375	100	120	1
Q0957	1200	24	3.200	2.480	4.000	1.375	100	120	1
Q0958	1200	32	5.120	3.969	3.000	1.375	100	120	1
Q0959	1200	32	5.340	4.139	4.000	1.375	100	120	1
Q0797	1500	29	3.720	2.883	3.000	1.660	100	120	1
Q0961	1500	29	4.000	3.100	4.000	1.660	100	120	1
Q0962	1500	40	6.310	4.891	3.000	1.660	100	120	1
Q0963	1500	40	6.700	5.193	4.000	1.660	100	120	1

ACCESORIOS FARM / FARM ACCESSORIES / ACCESSOIRES FARM



Ref.

Q0349

Suspensión con cable de acero
Steel cable suspension
Suspension avec câble en acier



Q0401

Bridas de acero inoxidable
Stainless steel clamps
Colliers inox antivandalisme



Q0159

Bridas de acero cincado
Zinc-plated steel clamps
Colliers en acier galvanisé



Q0158

Brida de metacrilato
Antivandalic acrylic
Colliers en méthacrylate



Q0657

Tapa acero INOX 316
Stainless Steel 316 end caps
Embouts INOX 316

LÍNEA CONTINUA

CONTINUOUS LINE CONNECTION

CÂBLAGE TRAVERSANT

3 polos / 3 poles / 3 pôles

Ref. Q0570

5 polos / 5 poles / 5 pôles

Ref. Q0571

DALI

EMERGENCY
1h/3h

Ref.

Q0978

Sujeción a báculo
Pole adapter
Adaptateur de lampadaire






RG 0/1	MACADAM 3/4	UGR <19	CR>80	L70B50 > 72.000	IK10	IP69K	CE EN 60598-1
--------	----------------	------------	-------	-----------------------	------	-------	------------------



VERSIÓN ESPECIAL ALTAS TEMPERATURAS (Hasta 80°C Ta).
SPECIAL HIGH TEMPERATURES VERSION (Up to Ta 80°C).
VERSION SPÉCIALE POUR HAUTES TEMPÉRATURES (jusqu'à 80°C)



Ref.	Tamaño Fuente Luz Light Source Size Dimension	Potencia Power Puissance	Emisión bruta Gross output Flux de la source	Emisión Neta Net output Flux sortant	Tª color Tª colour Tª couleur	L	D	D + brida D + clamp D + fixations	Embalaje Packaging Emballage
	(mm)	(W)	(Lm)	(Lm)	(°K)	(mm)	(mm)	(mm)	
Q0955K	560	17	2.224	1650	5.000	763	100	120	1
Q0959K	1120	34	4448	3300	5.000	1.375	100	120	1
Q0963K	1400	43	5560	4125	5.000	1.660	100	120	1



TUBO DIFUSOR EN PMMA ESPECIAL CON CERTIFICACIÓN FDA PARA INDUSTRIA ALIMENTARIA.
 DIFFUSER MADE IN FDA CERTIFIED PMMA SPECIAL FOR FOOD INDUSTRY.
 TUBE DIFFUSEUR EN PMMA SPÉCIAL AVEC CERTIFICATION FDA POUR L'INDUSTRIE ALIMENTAIRE.

